



## MARQUIS® STUDENT KD LOCKERS

Since 1983, Superior® Marquis Student KD lockers are the most specified single-point lockers in the marketplace. Designed with superior features usually reserved for heavy-duty athletic lockers, our sixth generation Marquis Student locker is an engineering achievement.



### FEATURES

**BODY CONSTRUCTION:** Knock down (KD) with 24 gauge solid body components

**DOORS:** 14 gauge plain doors with 18 gauge full-height door stiffener are standard. Louvered, Security-Plus and diamond perforated door styles are available

**FRAME:** 16 gauge frame with 16 gauge horizontal cross member between doors on double and triple tier wardrobe lockers

**HANDLE:** Deep-drawn seamless stainless steel recessed handle

**DOOR STRIKE:** Continuous vertical door strike at both hinge and latch side

**LATCHING:** Single-point maintenance-free quiet, 11 gauge latch hooks MIG welded to frame

**HINGES:** 16 gauge continuous piano type is standard. Heavy-duty 13 gauge 3-1/2" 7-knuckle hinges are available as an upgrade

**HOOKS:** 2-single hooks and 1-double hook is standard. 1- double hook only for triple tier and 1-double and 1-single hook for 9" wide openings 30" and higher

**SHELVES:** Hat shelf for single tier openings 60" and 72" high

**NOTES:** All production KD lockers are supplied without legs unless otherwise specified.

**SIZES:** See wardrobe locker chart on page 34 for sizes

**WARRANTY:** 2 years

### MAXoption

**UPGRADES** all body components to 16 gauge with 18 gauge back. Recommended when placing heavy items in lockers such as backpacks.



**STANDARD**  
 Deep-drawn stainless steel recessed handle with single-point latching



**STANDARD**  
 11 gauge single-point latch is MIG welded to frame



**STANDARD**  
 16 gauge continuous piano hinge



**STANDARD**  
 Marquis Student Lockers include a 3" wide 18 gauge full height door stiffener spot welded to the inner door face and MIG welded to the hinge side as well as to the top and bottom door flanges providing a rigid torque-free door. A 1-1/2" wide stiffener will be furnished for 9" wide Marquis doors.

## MARQUIS® STUDENT LOCKER SPECIFICATIONS

**General:** Lockers shall be "Superior Marquis Student KD Lockers" as manufactured by List Industries Inc. or approved equal. Fabricate lockers square, rigid and without warp, with metal faces flat and free from dents or distortion. Make all exposed metal edges safe to touch. Weld frame members together to form rigid, one-piece structure. Weld, bolt, or rivet other joints and connections as standard with manufacturer. Grind exposed welds flush. Do not expose bolts or rivet heads on fronts of locker doors or frames except for fastening of number plates and recessed handle.

**Finishing:** All locker parts to be cleaned and coated after fabrication with a seven stage zinc/iron phosphate solution to inhibit corrosion, followed by a coat of high grade custom blend powder electrostatically sprayed and baked at 350 degrees Fahrenheit for a minimum of 20 minutes to provide a tough durable finish. Color to be selected from manufacturer's standard list of colors. Body components to be painted #729 Parchment. Two-tone color combination shall be at no additional cost with the locker frame and trim chosen from one color and the doors may be one of any other color chosen from manufacturer's standard selection.

**Frame:** Fabricate of 16 gauge (minimum) channels, with integral continuous door stop/strike formed on both latch and hinge side vertical members. Cross frame members of 16 gauge channel shapes, including intermediate cross frame members on double and triple tier (frames with doors over 18" high) lockers shall be securely welded to the vertical framing members to ensure rigidity. Rubber bumpers shall be provided to cushion door closing.

**Marquis Student Wardrobe Doors:** Doors 20" high and over to be fabricated from single sheet prime 14 gauge steel with single bends at top and bottom and double bends at the sides. Doors shall include a 3" wide (1-1/2" for 9" wide doors) 18 gauge full height channel door stiffener MIG welded to the hinge side of the door as well as to the top and bottom door return bends and spot welded to the inside of door face to form a rigid torque-free box reinforcement for the door. Doors shall be plain (non-louvered). Wardrobe doors shall include ventilating perforations in the top and bottom door flanges.

**Marquis Seamless Drawn Locker Handle:** All wardrobe doors 20" and higher shall have a seamless drawn not less than 304, stainless steel not less than 304 recessed handle shaped to receive a padlock or built-in combination lock. The recessed handle shall be deep enough to have the lock be completely flush with the outer door face.

**Marquis Latch Assembly:** Shall be single point rigid non-moving positive latch by means of a heavy 11 gauge (minimum) latch securely welded to the 16 gauge vertical frame member. The latch assembly must be made of a single piece of steel and have a padlock loop that inserts through the recess pan. The latch must be able to accept either a padlock or built-in combination lock. A rubber bumper shall be securely attached to the latch.

**Door Hinges:** Hinges shall not be less than 16 gauge continuous piano type riveted to frame and welded to the door. All doors shall be right hand side hinged.

**Body:** Fabricate back and sides of 24 gauge (minimum) sheet steel, with double flanged connections extending full height. Form top, bottom and intermediate tier dividers of 24 gauge (minimum) sheet steel with single return bends at all sides. Bolt top and bottom as well as horizontal tier dividers of wardrobe openings to front horizontal frame members at not less than one place in addition to side panels. Form hat shelves at 60" and 72" high single tier lockers of 24 gauge (minimum) sheet steel with single bends at sides and back and a double bend at front.

**Locks (If Required):** Shall be master keyed to one system for the entire project. (Go to [www.ListIndustries.com](http://www.ListIndustries.com) for lock use chart and suggested lock application). Padlock only for 9" wide lockers.

**Equipment:** Openings 60" and 72" shall include one hat shelf. One double hook and two single hooks are standard with the following exceptions:

- Openings 20" and 24" high: One double hook only.
- Openings 9" wide: One double and one single hook only for openings 30" and higher.

**Two-Year Warranty:** Superior KD lockers are covered against all defects in materials and workmanship excluding finish, damage resulting from deliberate destruction and vandalism under this section for a period of two years.