

LOCKER DETAILS:

DOOR & FRAME COLOR =

BODY COMPONENT COLOR = 729 PARCHMENT

TOP :

HANDLE = LIFT (S.S. RECESSED DRAWN)

DOOR VENTILATION = 3' LOUVERS

SIDE VENTILATION = SOLID

BASE =

HINGE = CONTINUOUS PIANO HINGE

CONTRACTOR NOTE

ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4' FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL.

## GAUGES

DODR = 14 GA., C.R.S.
FRAME = 16 GA., C.R.S.
TOP = 24 GA., C.R.S.
BOTTOM = 24 GA., C.R.S.
SHELVES = 24 GA., C.R.S.
SIDES = 24 GA., C.R.S.
BACKS = 24 GA., C.R.S.

LATCHING (WARDROBE) THREE POINT RECESSED ON LOCKER
DOORS 48' AND OVER, TWO POINT RECESSED ON
ON LOCKER DOORS 36' TO 20'. AUTOMATIC
LOCKING DEVICE WITH LIFT-TYPE PADLOCK HASP.

SIDE VIEW

FRONT VIEW



THE DRAWING AND THE INCOMMETERS ON IT TO THE ORDERS STATE
THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL
PROPERTY OF LIST INDUSTRIES, INC. AND SHALL NOT BE COPIED OR
DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION. ONLY LIST INDUSTRIES
RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED
MODIFICATIONS RELEASES LIST INDUSTRIES FROM ALL LIABILITIES.
TOLERANCES UNLESS SPECIFIED
FRACTIONS: ±1/32 DECIMALS: ±.010 DEGREES: ±1*

	Customer: CUSTOMER	Drawn By: DRAFTER	Checked By:	Date: DA	TF	Scale:	ONE
ļ	Customer Order Number: PO#				IIL .		
	Description: IOD NAME	Acad Number: PAG	e number		Sheet #	Of #	Revision:
		Drawing Number:	FOLDER	NUMBE	ER .		