

LIST "HEAVY DUTY CORRIDOR" K.D. TRIPLE TIER LOCKER (9" TO 15" WIDE) (PRODUCT No. HDC _ _ _ _ _ -3_)

FLEVATION ' '



SIDE VIEW



FRONT VIEW

DEGREES: ±1°

INCKER DETAILS:

DOOR & FRAME COLOR =

BODY COMPONENT COLOR = 729 PARCHMENT

TOP =

HANDLE = LIFT (S.S. RECESSED DRAWN)

DOOR VENTILATION = 3' LOUVERS

SIDE VENTILATION = SOLID

BASE = LOCKS =

HINGE = CONTINUOUS PIANO HINGE

CONTRACTOR NOTE

ALL CONCRETE BASES SHOULD BE LEVEL AND TROVELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4" FROM THE TOP EDGE OF THE BASE, LOCKERS MUST BE ANCHORED TO WALL.

GAUGES

DOOR = 14 GA., C.R.S. FRAME = 16 GA., C.R.S TOP = 24 GA., C.R.S. $B\Box TT\Box M = 24 GA., C.R.S.$ SHELVES = 24 GA., C.R.S. SIDES = 24 GA., C.R.S. BACKS = 24 GA., C.R.S.

LATCHING: (WARDROBE) TWO POINT RECESSED AUTO-MATIC LOCKING DEVICE WITH LIFT-TYPE PADLOCK HASP, 36" TO 20" TALL DOORS.

Date:

DATE

Sheet # Of #



THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF LIST INDUSTRIES, INC. AND SHALL NOT BE COPIED OR DISCLOSED TO OTHERS VITHOUT VRITTEN PERMISSION. ONLY LIST INDUSTRIES RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES LIST INDUSTRIES FROM ALL LIABILITIES. TOLERANCES UNLESS SPECIFIED

DECIMALS: ±.010

FRACTIONS: ±1/32

Checked By: Drawn By: Customer: CUSTOMER DRAFTER Customer Order Number: PO# Acad Number: PAGE NUMBER Description: JOB NAME Drawing Number: FOLDER NUMBER JOB LOCATION

Revision:

NONE