

LOCKER DETAILS:

DOOR & FRAME COLOR =

BODY COMPONENT COLOR = 729 PARCHMENT OR 725 HALLOWELL GRAY

TOP =

HANDLE = LIFT (S.S. RECESSED DRAWN) DOOR VENTILATION = 5/8" x 1-1/2" DIAMOND SIDE VENTILATION = 5/8" x 1-1/2" DIAMOND

BASF = TUCKS =

HINGE = CONTINUOUS PIANO HINGE

CONTRACTOR NOTE

ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4' FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL.

GAUGES

DOOR = 14 GA., C.R.S. 16 GA., C.R.S FRAME = TOP = 16 GA., C.R.S. BOTTOM = 16 GA., C.R.S. SHELVES = 16 GA., C.R.S. SIDES = 16 GA., C.R.S. BACKS = 18 GA., C.R.S.

Drawn By:

DRAFTER

Drawing Number:

LATCHING: (WARDROBE) TWO POINT RECESSED AUTO-MATIC LOCKING DEVICE WITH LIFT-TYPE PADLOCK HASP, 36" TO 20" TALL DOORS.

SIDE VIEW

00000000

FRONT VIEW

Customer: CUSTOMER



THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL
PROPERTY OF LIST INDUSTRIES, INC. AND SHALL NOT BE COPIED OR
DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION. ONLY LIST INDUSTRIES
RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED
MODIFICATIONS RELEASES LIST INDUSTRIES FROM ALL LIABILITIES.
THI FRANCES LINI ESS SPECIFIED

FRACTIONS: ±1/32

DECIMALS: ±.010

DEGREES: ±1*

Customer Order Number: PO# Description: JOB NAME JOB LOCATION

Checked By: NONE DATE Acad Number: PAGE NUMBER Sheet # Of # Revision: FOLDER NUMBER