

LOCKER DETAILS:

EXTERIOR COLOR =

INTERIOR COLOR = SAME AS EXTERIOR

TOP =

HANDLE = SINGLE POINT (S.S. RECESSED DRAWN)
DOOR VENTILATION = 7/16' x 15/16' DIAMOND
SIDE VENTILATION = 1/2' 13 GA. FLT/EXP/MTL

BASE =

LOCKS =

HINGE = 7-KNUCKLE, 13 GA. BUTT HINGE WELDED TO DOOR & RIVETED TO FRAME

CONTRACTOR NOTE

ALL CONCRETE BASES SHOULD BE LEVEL AND TROVELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4' FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL.

GAUGES

DOOR = 14 GA., C.R.S. STIFFENER = 18 GA., C.R.S. FRAME = 16 GA., C.R.S. TOP = 16 GA., C.R.S. BOTTOM = 16 GA., GALV

BOTTOM = 16 GA., GALVANNEAL HAT SHELVES = 16 GA., GALVANNEAL INT/MED SHELVES = 16 GA., GALVANNEAL

SIDES = 1/2" 13 GA. FLT/EXP/MTL, H.P.O

BACKS = 18 GA., C.R.S.

LATCHING: (BOX DOOR) SINGLE POINT RECESSED
LOCKING DEVICE PREPARED FOR BOTH
PADLOCK AND BUILT-IN LOCKS.

HINGES: (BOX DOOR) TWO HINGES ON LOCKER DOORS 36" AND UNDER.

SIDE VIEW

TW FRONT VIEW

SUPERIOR

THIS DRAYING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF LIST INDUSTRIES, INC. AND SHALL NOT BE COPIED OR DISCLOSED TO OTHERS VITHOUT VRITTEN PERMISSION. ONLY LIST INDUSTRIES RESERVES THE RIGHT TO ALTER ANY DESIGN. ANY UNAUTHORIZED MODIFICATIONS RELEASES LIST INDUSTRIES FROM ALL LIABILITIES.

TOLERANCES UNLESS SPECIFIED: FRACTIONS: ±1/32 DECIMALS: ±.010 Customer: CUSTOMER

Customer Order Number: PO#

Description:

DEGREES: ±1*

JOB NAME JOB LOCATION Checked By:

Drawn By:

DRAFTER

Acad Number: PAGE NUMBER

Date: DATE

NONE NONE

Sheet # 0f # Revision:

Scale:

Drawing Number: FOLDER NUMBER