

LOCKER DETAILS:

EXTERIOR COLOR =

INTERIOR COLOR = SAME AS EXTERIOR

HANDLE = SINGLE POINT (S.S. RECESSED DRAWN) DOOR VENTILATION = 7/16" x 15/16" DIAMOND

SIDE VENTILATION = 1/2" 13 GA. FLT/EXP/MTL BASE =

LOCKS =

HINGE = 7-KNUCKLE, 13 GA. BUTT HINGE WELDED TO DOOR &

RIVETED TO FRAME

CONTRACTOR NOTE

ALL CONCRETE BASES SHOULD BE LEVEL AND TROWELED SMOOTH TO ASSURE PROPER INSTALLATION OF THE LOCKERS. ALL FLOORING MATERIAL ATTACHED TO THE FACE OF THE BASE SHOULD BE RECESSED AT LEAST 1/4" FROM THE TOP EDGE OF THE BASE. LOCKERS MUST BE ANCHORED TO WALL.

GAUGES

14 GA., C.R.S. DOOR = STIFFENER = 18 GA., C.R.S. FRAME = 16 GA., C.R.S 16 GA., C.R.S. TNP = 16 GA. GALVANNEAL BUTTUM =

HAT SHELVES = 16 GA., GALVANNEAL

INT/MED SHELVES = 16 GA., GALVANNEAL 1/2" 13 GA. FLT/EXP/MTL, H.P.O

SIDES = BACKS = 18 GA., C.R.S.

LATCHING: (BOX DOOR) SINGLE POINT RECESSED LOCKING DEVICE PREPARED FOR BOTH PADLOCK AND BUILT-IN LOCKS.

HINGES: (BOX DOOR) TWO HINGES ON LOCKER DOORS 36" AND UNDER.

FRONT VIEW SIDE VIEW



THIS DRAWING AND THE INFORMATION ON IT IS THE CONFIDENTIAL PROPERTY OF LIST INDUSTRIES, INC. AND SHALL NOT BE COPIED OR DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION, ONLY LIST INDUSTRIES RESERVES THE RIGHT TO ALTER ANY DESIGN, ANY UNAUTHORIZED MODIFICATIONS RELEASES LIST INDUSTRIES FROM ALL LIABILITIES. TOLERANCES UNLESS SPECIFIED FRACTIONS: ±1/32 DECIMALS: ±.010 DEGREES: ±1°

Customer: CUSTOMER Customer Order Number: PO# Description: JOB NAME JOB LOCATION Drawn Bv. Checked By: DRAFTER DATE PAGE NUMBER Sheet # Of # Revision: Acad Number: Drawing Number: FOLDER NUMBER

MC-5 11-21-12

NONE